



CityCharge Mini2 Plus

Public charging station for electric vehicles

- 2 charging cables Type2 up to 2x22kW
- Compelling design
- Bright LED screen
- Robust aluminum casing
- Integrated energy meter
- RFID authorization
- 3G / 4G / WiFi / OCPP communication
- Elios.It web administration

Charge station can be used at:



Public parking



Underground garage



Office buildings



Shopping malls



CityCharge Mini2 Plus is classified as fast Mode 3 charging station with ability to provide up to 2x22 kW of power using Type 2-IEC62196 charging cables.

CityCharge Mini2 Plus is manufactured using the highest quality materials. The solid housing is made of extruded CNC machined and anodized aluminum parts that are designed to last.

Top quality electronics with integrated climate control ensures highest reliability even in the harsh weather conditions.

Bright animated LED screen and side bars are visible even in the direct sunlight, while giving modern impression and are seen from a distance at night.

Available as stand-alone model with a user-friendly RFID identification for small, local charging network or it can be integrated into existing charging network using Ethernet cable, 3G, 4G module or WiFi.

CityCharge Mini2 Plus



Technical specifications

Cable type

Type 2—IEC62196 (Mode 3)



Input power

3 or 1 phase 400 V/AC 50 Hz 32 or 16 A

Output power
(optional)

2x3-phase 400 V/AC 32 A (2x22 kW)

2x3-phase 400 V/AC 16 A (2x11 kW)

2x1-phase 230 V/AC 32 A (2x7,2 kW)

2x1-phase 230 V/AC 16 A (2x3,6 kW)

Communication
(optional)

3G / 4G Elios.cloud and OCPP 1.6 JSON

WiFi Elios.cloud and OCPP 1.6 JSON

Ethernet Elios.cloud and OCPP 1.6 JSON

Power management system

User interface

LED backlight screen

RFID user access control

LED status indication

3 Phase digital energy meter with backlight

Safety protection

Short circuit protection

Leakage current protection

Leakage current breaker auto reset (optional)

Other specifications

Operational temperature -30 °C to +50 °

IP54 electrical enclosure rating

IK10 vandalism-proof rating

Stainless aluminum housing

Dimensions 150 x 350 x 670

Weight 21 kg

UV resistant

CE certified